

World leaders in diving equipment technology

DEFENCE COMMERCIAL



Divex G11-4 Hyperbaric Oxygen Analyser

HEAD OFFICE

Enterprise Drive Westhill Aberdeen AB32 6TQ T: +44 (0)1224 740145 F: +44 (0)1224 740172 The Divex G11-4 Hyperbaric Oxygen Analyser measures partial pressure in Bar O_2 of diving chambers and hyperbaric environments. It is specifically designed to withstand harsh hyperbaric environments. Calibration is simple and is done by adjusting the trimmer on the front panel.

The Sensor: Fast response time of less than 6 seconds to 90% of the final reading. It is an electrochemical transducer; specific to oxygen which produces an electrical output signal proportional to the oxygen concentration adjacent to its sensing surface.

It is a temperature compensated sealed unit with no electrolyte to change or electrodes to clean. The cell is completely disposable and maintenance free.

Caution Against Rapid Pressure

Changes: Although the sensor is designed with a degree of protection against large pressure changes, it is strongly recommended that the instrument is not subjected to rapid compression or decompression, that any pressure changes be at the same rate that a human being can withstand. It should not be passed through chambers medical locks.

GLOBAL LOCATIONS

Aberdeen Chertsey Portsmouth Bremen Dubai Cape Town Perth Sydney

Specification

General	Range Resolution Display Power Operating Temperature Sensor Life Sensor Response Temperature Effect Flow Rate	0-2 Bar Bar ppO_2 \pm 1m Bar $3^{1}/_{2}$ digit LCD 15 mm high characters 1 x 9 volt battery (PP3, MN1604 etc) 0 - 50°C (32 - 122°F) 12 - 24 months in 21% O_2 at STP Less than 6 seconds to 90% of final reading Less than 5% of reading over temperature range 250 ml/min \pm 50 ml/min using flow adaptor
Dimensions	Length Width Height Weight	145 mm (5.7 in) 80 mm (3.2 in) 35 mm (1.4 in) 237 gm (8.3 oz)
Warranty	Instrument	1 year

discover more www.divexglobal.com

G11-4 Hyperbaric Oxygen Analyser

Order Code G11-4

Replacement Oxygen Sensor

Order Code SE5110S