

World leaders in diving equipment technology



Kinergetics Water Heater Electric (WHE-03)

DEFENCE COMMERCIAL

HEAD OFFICE

Enterprise Drive Westhill Aberdeen AB32 6TQ T: +44 (0)1224 740145 F: +44 (0)1224 740172

GLOBAL LOCATIONS

Aberdeen Chertsey Portsmouth Bremen Dubai Cape Town Perth Sydney

discover more www.divexglobal.com The Divex Electric Powered Water Heating Module, (WHE-03), has been designed and manufactured for use in professional diving systems. The system will heat and maintain control of the heated seawater within a temperature rise range of 0 to 50°C (32 to 122°F). The system incorporates a positive displacement pump, electric heaters and all electrical controls necessary to provide a complete water heating system for deep diving.

The WHE-03 assembly is comprised of a motor, pump, heater tank, pipework and a control panel. These components are mounted into a robust stainless steel frame. The system requires a constant supply of seawater and runs from a 440-480 V, 3-Phase, 60 Hz power supply. The output is heated seawater at pressures up to 68 bar and 45 litres/min.

The temperature control system of the WHE-03 has been designed to be simple and effective. The unit heats water in the heater tank using five banks of heater elements. These heater banks are controlled with five switches, mounted on the electrical enclosure. The banks of heaters are configured to deliver a variety of heating capacities depending on the combination of banks selected. When all five heater circuits are on the total output is 190 kW. The appropriate heater circuits must be selected manually according to the relative temperature rise required. A schedule is attached to the front of the control panel door indicating the heater banks to be used for the required temperature rise.

Specification

Shipping Weight Dry Weight Power Requirements
Input Fluid
Input Pressure
Input Flow
Output Pressure
Output Flow
Temperature Rise

Control Range

Temperature Control

580 kg 460 kg 440 VAC, 3-phase, 60 Hz, 150-190 kW, 210-250 A Fresh water or seawater 3.4 to 10 bar 45 litres/min minimum Up to 68 bar Up to 45 litres/min

0 to 50°C (32 to 122°F) ± 1°C (± 2°F)

Kinergetics Water Heater Electric Powered (WHE-03) 45LPM

Order Code KI40018AA

Kinergetics Water Heater Electric Powered (WHE-03) 380V

Order Code KI40018AB



Kinergetics Water Heater Electric Powered (WHE-03) c/w Remote Panel 440VAC

Order Code KI40018AC

Kinergetics Water Heater Electric Powered (WHE-03) Spares Kit

Order Code KI40018200