

DRYSUITS FOR CONTAMINATED WATER DIVING NEW FOR 2012











	VIKING PRO	VIKING PROTECH	VIKING HD
AREAS OF USE	Fire & Rescue, military, sports/technical	Fire & Rescue, military, sports/technical	Commercial, military
MATERIAL	NR/EPDM with 2-way stretch polyester lining. Total material weight: 1,000 \pm 100 g/m².	NR/EPDM with 4-way stretch polyamide/ elastane lining. Total material weight: $1,250 \pm 100$ g/m ² .	NR/EPDM with 2-way stretch polyester lining. Total material weight: 1,550 \pm 100 g/m².
SEAMS	Internal taped & stitched. External vulcanized.	Internal taped & stitched. External vulcanized.	Internal taped & stitched. External vulcanized.
COLOUR	Red with black reinforcements or all black.	All black (military Combat version has black logos).	Red with black reinforcements or all black.
SIZE RANGE	 00/SML, 01/MED, 02/LGE, 03/EXL, 04/XXL, 05/XXXL 00/SML-05/XXXL Wide 00/SML-05/XXXL D Wide 	 00/SML, 01/MED, 02/LGE, 03/EXL, 04/XXL, 05/XXXL 00/SML-05/XXXL Wide 00/SML-05/XXXL D Wide 	• 01/MED, 02/LGE, 03/EXL, 04/XXL • 01/MED Wide-04/XXL Wide
REINFORCEMENTS	Shoulders and arms. Crotch, across the seat area and extending down to the front of the legs and down across the boots. Fin strap keeper on boots.	Shoulders and arms. Crotch, across the seat area and extending down to the front of the legs and down to the front of the neoprene boots. Fin strap keeper on boots.	Across shoulders and down the arms. Reinforced crotch. Above knees, down the legs and across the boots.
ZIPPER	90 cm HD zipper Non-mag version on black suits	 90 cm medium duty non-mag zipper on rear entry suits 85 cm medium duty non-mag zipper on front entry versions * 	90 cm HD zipper Non-mag version on black suits
VALVES	Push protected inlet valveViking X2 exhaust valveStandard hose	Push protected inlet valveLow profile exhaust valveStandard hose	Push protected inlet valveViking X2 exhaust valveStandard hose
ACCESSORIES	 Range of hoods and neck seal options Rubber cuff ring or bayonet ring system Rubber pocket options Relief zip Nitrile safety boots, PVC wellies or neoprene boots Dry glove options including latex or rubber gloves Rubber or latex mittens 	 Range of hoods and neck seal options Rubber cuff ring or bayonet ring system Rubber pocket options Relief zip Nitrile safety boots or PVC wellies Dry glove options including latex or rubber gloves Rubber or latex mittens 	 Range of hoods, neck seals and helmet yokes Rubber cuff ring or bayonet ring system Rubber pocket options Relief zip Nitrile safety boots or PVC wellies Dry glove options including latex or rubber gloves Rubber or latex mittens
CERTIFICATION & APPROVALS	• EN 14225-2:2005 • BIO approval	 EN 14225-2:2005 BIO approval New PROTECH BE NAVY suit, fitted with HD zipper, also has HZ chemical approval 	EN 14225-2:2005HZ chemical approvalBIO approval

^{*} Front entry version available to special order only.







		J	
	VIKING HDS	VIKING DD	VIKING HAZTECH
AREAS OF USE	Fire & Rescue, police, hazmat, military, commercial	Commercial helmet diving	Fire & Rescue, contaminated water diving, warm water/climate diving
MATERIAL	NITECS NBR/EPDM blend on knitted black polyester stretch lining. Total material weight: $1,050 \pm 100 \text{ g/m}^2$.	NR/EPDM with 2-way stretch polyester lining. Total material weight: 1,550 \pm 100 g/m².	TPU (thermoplastic polyurethane), single coated onto a black knitted nylon fabric. Total material weight: 483 g/m².
SEAMS		Internal tanad 8 atitahad External vulganizad	
SEAMS	Internal taped & stitched. External vulcanized.	Internal taped & stitched. External vulcanized.	High frequency welded. Taped on the inside for visual appearances.
COLOUR	Black with black NITECS reinforcements.	Red with black reinforcements or all black.	Red with black reinforcements.
SIZE RANGE	 00/SML, 01/MED, 02/LGE, 03/EXL, 04/XXL, 05/XXXL 00/SML-05/XXXL Wide 00/SML-05/XXXL D Wide 	• 01/MED, 02/LGE, 03/EXL, 04/XXL	 00/SML, 01/MED, 02/LGE, 03/EXL, 04/XXL 00/SML-04/XXL Wide 00/SML-04/XXL D Wide
REINFORCEMENTS	Shoulders and arms. Crotch, across the seat area and extending down to the front of the legs and down across the boots. Fin strap keeper on boots.	Additional layers of rubber are added to the legs from above the knees and down to the boots, which have a soft sole.	A 1 mm PU film is welded onto shoulders and elbows. The knee area is similarly protected.
ZIPPER	• 90 cm HD zipper	None Neck entry through the collar	 90 cm medium duty zipper made from a TPU coated fabric High frequency welded to the suit
VALVES	Viking Hazmat inlet valveViking X2 exhaust valveStandard hose	None. All functions are handled through the helmet.	Push protected inlet valveViking X2 exhaust valveStandard hose
ACCESSORIES	 HDS Magnum hoods and yokes for contaminated water diving HDS rubber cuff ring system Rubber pocket options Relief zip Nitrile safety boots or PVC wellies Dry glove options including latex or rubber gloves Rubber or latex mittens 	 Range of collars to fit the most popular classic helmets Rubber cuff ring system Rubber pocket options Relief zip Nitrile safety boots or PVC wellies Dry glove options including latex or rubber gloves Rubber or latex mittens 	 Latex or neoprene hood, or HDS Magnum hoods and yokes for contaminated water diving Quick connect collar system HDS rubber cuff ring or bayonet ring system PU bellows pockets Nitrile safety boots, PVC wellies or neoprene boots
CERTIFICATION & APPROVALS	EN 14225-2:2005HZ chemical approvalBIO approval	EN 14225-2:2005HZ chemical approvalBIO approval	EN 14225-2:2005HZ chemical approvalBIO approval

