ATT-400 Series Acoustic Target Transponder



- Easy to Deploy
- Operates as Transponder or Pinger
- Range of 750 to 1800 meters
- Operational for 6 months





The ATT-400 series transponders are a small battery operated underwater acoustic device that can operate as a transponder or pinger. When programed as a transponder, the ATT-400 works with the DTI-300 or VDAR receivers to mark and relocate targets underwater in ranges of 1000 meters(3330ft). A manual ON/OFF switch or water switch actives the transponder where it can remain in the receive mode for up to 6 months waiting quietly from an interrogation signal for the DTI-300 or VDAR Diver Transponder Interrogator.

In addition, the ATT-400 can be program to operate as a acoustic pinger with eight user selectable frequencies from 27Khz to 34Khz. With a 2 watt output, the ATT-400 provides ranges of up to 1800 meters with a standard receivers like the or PRS-275.

Constructed of non corrosive material, the ATT-400 can be deployed to depth of 6000 meters.

SPECIFICATIONS

Receive Frequency User Selectable Transmit Frequency Acoustic Output	26Khz 27,28,29,30,31,32,33, 34Khz 180db
Acoustic Signal	Coded
System Range	
Transponder Mode	750 meters
Pinger Mode	1800 meters
Activation	Manual ON/OFF or Water
Switch	
Battery	(2) 9 Volt Battery, Alkaline
Operational Life:	10 hours to 6 months
Depth Rating	
ATT-400	100m (328ft)
ATT-400/1KM	1000m (3280ft)
ATT-400/6KM	6000m(19,685ft)
Housing	
ATT-400	Delrin
ATT-400/1KM	Aluminum Hard Anodized
ATT-400/6KM	Aluminum Hard Anodized
Size	
ATT-400	21cm(L) X 6.4cm(D)
ATT-400/1KM	24cm(L) X 6.4cm(D)
ATT-400/6KM	24cm(L) X 6.4cm(D)
Weight	
ATT-400	In Air: 0.37Kg
ATT-400/1KM	In Air: 0.65Kg

In Air: 0.70Kg

Specifications are subject to change without notice

ATT-400/6KM

RJE International, Inc. 15375 Barranca Parkway, Suite B107, Irvine, CA 92618 Tel: (949)727-9399 Fax: (949)727-0070 E-mail: sales@rjeint.com Web Page: www.rjeint.com

ATT400 rev B 1/12